XAMV HF SD HIGH-FLOW

Vertical multistage pump with electronic system HIGH-FLOW

NEW




Description

Up/Down technology for submersed, surface or underground installation.
Automatic system of water supply and dry-running protection.
Antiblocking system every 72 hours of pump inactivity.
Protection rating IP 68.



Technopolymer check valve with flow control disc and spring in AISI 316 standard equipment



Applications

- Domestic boosting
- Medium sprinkling and surface irrigations
- Industrial washing and cooling
- Systems for potable water treatment

Pumped liquid:
Clean water with no abrasive or suspended solids
Liquid temperature +2°C ÷ +40°C
Air temperature max +45°C
Depth max 5 m
Calibrating pressure rate switch 2.2 bar

Materials

- Motor body and pump body: Stainless steel AISI 304
- Special technopolymer flanges
- Shaft: Stainless steel AISI 420
- Diffuser and impellers: Noryl
- Rear cap: Stainless steel AISI 304
- Dumping feet: Rubber
- Mechanical seal: Graphite / ceramic
- Oil chamber on the mechanical seal
- A2 Stainless steel bolts
- NBR70 O-ring
- H07RN8-F Electric cable 10 m length with Schuko plug
- Tropicalized circuit board in compliance with the RoHS directive
- Class F insulated motors

	Code	P_2 Nom.		1 ~ 50Hz Amp.	3 ~ 50Hz Amp.		Cap µF	Stages	Q (lt/m) Flow							Dimensions mm						Wgt. kg
		Hp	kW	230 V	230 V	400 V			0	30	50	70	100	120	145	A	H1	H	N	DNM	DNA	
									Total Hm in CA													
AUTO MONO	XAMV1204HFSD	1,2	0,90	6,4	-	-	25	4	43	38	34	30	24	16	6	560	95	226	200	1"¼	1"¼	19,5
	XAMV1505HFSD	1,5	1,10	7,3	-	-	30	5	51	46	43	38	30	21	9	715	95	226	200	1"¼	1"¼	21,5
	XAMV2006HFSD	2,0	1,50	10,1	-	-	40	6	62	55	51	45	34	24	10	715	95	226	200	1"¼	1"¼	23
MAN MONO	XMV1204HFSD	1,2	0,90	6,4	-	-	25	4	43	38	34	30	24	16	6	560	95	226	200	1"¼	1"¼	19,5
	XMV1505HFSD	1,5	1,10	7,3	-	-	30	5	51	46	43	38	30	21	9	715	95	226	200	1"¼	1"¼	21,5
	XMV2006HFSD	2,0	1,50	10,1	-	-	40	6	62	55	51	45	34	24	10	715	95	226	200	1"¼	1"¼	23
MAN THR	XMV1204THFSD	1,2	0,90	-	3,1	2,2	-	4	43	38	34	30	24	16	6	560	95	226	200	1"¼	1"¼	19,5
	XMV1505THFSD	1,5	1,10	-	3,5	2,5	-	5	51	46	43	38	30	21	9	715	95	226	200	1"¼	1"¼	21,5
	XMV2006THFSD	2,0	1,50	-	4,2	3,0	-	6	62	55	51	45	34	24	10	715	95	226	200	1"¼	1"¼	23

Curves and performance η = 2900 1/min

